

IN THE CLAIMS

This listing of the claim will replace all prior versions and listings of claim in the present application.

Listing of Claims

1. (currently amended) An automatic frequency control signal generating circuit comprising:
 - a first frequency error detection unit for extracting from an input signal at least two known different symbols as a first symbol set, detecting a frequency error of said input signal based on the ~~basis of~~ said extracted first symbol set, and delivering said frequency error;
 - a second frequency error detection unit for extracting from said input signal at least two known symbols having a symbol distance different from that of said first symbol set as a second symbol set, detecting a frequency error of said input signal based on the ~~basis of~~ said extracted second symbol set and delivering said frequency error;
 - a decision unit for deciding which one of the ~~outputs of~~ said first and second frequency error detection units is selected; and
 - a control signal unit for generating a control signal adapted to control the frequency of said input signal based on the ~~basis of the~~ an output of one of said first or second frequency error detection ~~unit~~ units selected by said decision unit.

2. (currently amended) An automatic frequency control signal generating circuit according to claim 1, wherein said control signal unit includes:

a positive/negative decision unit for deciding whether the output of any one of said first and second frequency error detection units selected by said decision unit is a positive value or a negative value and delivering a result of a decision by said positive/negative decision unit; and

an accumulating unit for accumulating the a value delivered out of said positive/negative decision unit and delivering an integrated signal as said control signal.

3. (currently amended) An automatic frequency control signal generating circuit according to claim 2, wherein said decision unit compares a predetermined reference value with an absolute value of the respective output values of said first and second frequency error detection units unit and selects effects detection of an output of any one of said first and second frequency error detection units in accordance with a comparison result.

4. (currently amended) An automatic frequency control signal generating circuit according to claim 3, wherein a frame format of said input signal includes a known pilot signal, a data area of predetermined symbol length and a known synchronous word symbol area of predetermined symbol length,

wherein said first frequency error detection unit extracts at least two synchronous word symbols in said synchronous word symbol area, and said second frequency error detection unit extracts said pilot signal and a synchronous word symbol in said synchronous word symbol area.

5. (currently amended) An automatic frequency control signal generating circuit according to claim 1, wherein said first frequency error detection unit includes:

a first multiplier for calculating and delivering a product of one symbol of said first symbol set and a complex conjugate of said symbol;

a first ~~phase inverter~~complex conjugate unit for inverting and conducting a complex conjugate of said symbol, and delivering the a phase of the product value delivered out of said first multiplier;₁

a second multiplier for calculating and delivering a product of another symbol of said first symbol set and a complex conjugate of said symbol;₁

a third multiplier for performing complex multiplication of the output of said phase inverter and the value-product delivered out of said second multiplier and delivering a complex product;₁ and

a first phase detection unit for detecting the phase of the output of said third multiplier and delivering said detected phase as said first frequency error; and wherein

wherein said second frequency error detection unit includes:

a fourth multiplier for calculating and delivering a product of one symbol of said second symbol set and a complex conjugate of said symbol;₁

a second complex conjugate unit ~~phase inverter~~-for inverting and conducting a complex conjugate of said symbol, and delivering the a phase of the value-product delivered out of said fourth multiplier;₁

a fifth complex multiplier for calculating and delivering a product of another symbol of said second symbol set and a complex conjugate of said symbol;₁

a sixth multiplier for performing complex multiplication of the output of said phase inverter and the ~~value-product~~ delivered out of said fifth complex multiplier and delivering a complex product;₁ and

a second phase detection unit for detecting the phase of the output of said sixth complex multiplier and delivering said detected phase as said second frequency error.

6. (currently amended) An automatic frequency control signal generating circuit according to claim 5, wherein one symbol of said first symbol set ~~inputted-input~~ to said first multiplier and another symbol of said first symbol set ~~inputted-input~~ to said second multiplier are located at positions which are distant from each other by n symbols in said input signal, where n is the a power of 2.

7. (currently amended) An automatic frequency control signal generating circuit according to claim 5, wherein the ~~the~~ a frame format of said input signal includes a data area of predetermined symbol length and a known synchronous word symbol area of predetermined symbol length, one symbol of said first symbol set inputted to said first multiplier is an initial synchronous word symbol of said synchronous word symbol area, another symbol of said first symbol set inputted to said second multiplier is one synchronous word symbol selected from a second and ensuing synchronous

word symbols of said synchronous word symbol area, and said first frequency error detection unit further includes a switch unit for selecting and delivering one desired synchronous word symbol from the second and ensuing synchronous word symbols of said synchronous word symbol area of said input signal.

8. (currently amended) An automatic frequency control signal generating circuit according to claim 7, wherein one symbol to be selected from the second and ensuing synchronous word symbols by means of said switch unit is located at a position which is distant from said initial synchronous word symbol by n symbols, where n is the a power of 2.

9. (currently amended) An apparatus for receiving signals having the automatic frequency control signal generating circuit as recited in claim 1, further comprising:

an RF receiving circuit for performing frequency conversion of a received signal, converting the received signal subjected to the frequency conversion into a digital signal and delivering it;

an oscillator for delivering to said RF receiving circuit a reference frequency signal for the frequency conversion;

a quadrature detector for converting the received signal subjected to the digital conversion into a baseband signal and delivering it;

a filter for eliminating unwanted frequency components of the received baseband signal and delivering a resulting signal;

a frequency corrector for correcting an error between the frequency of the baseband signal delivered out of said filter and the frequency of said reference frequency signal on the basis of said control signal from said automatic frequency control signal generating circuit and delivering a corrected baseband signal;

a demodulator for demodulating and delivering the baseband signal received from said frequency corrector; and

a buffer for holding the corrected baseband signal output of said frequency corrector, wherein

wherein said automatic frequency control signal generating circuit extracts said first and second symbol sets from said input signal now represented by the corrected baseband signal held in said buffer and generates said control signal on the basis of said symbol sets to supply said control signal to said frequency corrector.

10. (currently amended) A radio base station apparatus comprising:

the receiving apparatus as recited in claim 9; and, further comprising:

a radio transmitting circuit for converting a signal of baseband zone to be transmitted, which signal is converted to an analog signal, into a signal of radio frequency band based on the basis of the reference frequency signal of said oscillator.

11. (currently amended) A radio transmitting/receiving system ~~for signals comprising:~~

the radio base station as recited in claim 10; ~~and, further comprising:~~
at least one mobile radio transmitting/receiving apparatus,
wherein said at least one mobile radio transmitting/receiving apparatus
receives a transmitting signal from said radio base station and controls a
reference frequency signal inside said mobile radio transmitting/receiving
apparatus based ~~on the basis of~~ a reference frequency signal extracted from
said received signal.

12. (currently amended) An apparatus for receiving signals
having the automatic frequency control signal generating circuit as recited in
claim 1, further comprising:

an RF receiving circuit for performing frequency conversion of a
received signal, converting the received signal subjected to the frequency
conversion into a digital signal and delivering ~~it~~ the received signal;

an oscillator for delivering to said RF receiving circuit a reference
frequency signal for the frequency conversion;

a quadrature detector for converting the received signal subjected to
digital conversion into a baseband signal and delivering it;

a filter for eliminating unwanted frequency components from the
received baseband signal and delivering a resulting signal;

a demodulator for demodulating and delivering the baseband signal
received from said filter; and

a buffer for holding the output of said filter ~~frequency corrector~~,

wherein said automatic frequency control signal generating circuit
extracts said first and second symbol sets from said input signal now

represented by the signal held in said buffer and generates said control signal based on the basis of said symbol sets, and said receiving apparatus further includes a frequency controller for controlling said reference frequency signal of said oscillator based on the basis of said control signal from said automatic frequency control signal generating circuit.

13. (currently amended) A radio terminal apparatus comprising:

the receiving apparatus as recited in claim 12; and, further comprising:
a radio transmitting circuit for converting a signal of baseband zone to be transmitted, which signal is converted into an analog signal, into a signal of radio frequency band based on the basis of the reference frequency signal of said oscillator.

14. (currently amended) A frequency error detection method comprising the steps of:

- a) ~~a step of~~ extracting at least two known different symbols as a first symbol set from an input signal;
- b) ~~a step of~~ calculating and delivering a product of one symbol of said first symbol set and a complex conjugate of said symbol;
- c) ~~a step of~~ inverting and delivering the phase of the output in said step b);
- d) ~~a step of~~ calculating and delivering a product of another symbol of said first symbol set and a complex conjugate of said symbol;

e) ~~a step of performing~~ complex multiplication of the outputs in said steps c) and d) and delivering a product; and

f) ~~a step of detecting~~ the phase of the output in said step e) and delivering said detected phase as a first frequency error of said input signal.

15. (currently amended) A frequency error detection method according to claim 14, wherein one symbol of said first symbol set in said step b) and another symbol in said first symbol set in said step d) are located at positions which are distant from each other by n symbols inside said input signal, where n is ~~the~~ a power of 2.

16. (currently amended) A frequency error detection method according to claim 14, wherein when ~~the~~ a frame format of said input signal includes a data area of predetermined symbol length and a known synchronous word symbol area of predetermined symbol length, one symbol of said first symbol set in said step b) is ~~the~~ a initial synchronous word symbol of said synchronous word symbol area and another symbol of said first symbol set in said step d) is one synchronous word symbol desirably selected from the second and ensuing synchronous word symbols of said synchronous word symbol area.

17. (currently amended) A frequency error detection method according to claim 14 further comprising the steps of:

g) ~~a step of extracting~~, as a second symbol set, at least two known symbols having a different symbol distance ~~from~~ from that in said first symbol set from said input signal;

h) ~~a step of calculating~~ and delivering a product of one symbol of said second symbol set and a complex conjugate of said symbol;

i) ~~a step of inverting~~ and delivering the phase of the value delivered in said step h);

j) ~~a step of calculating~~ and delivering a product of another symbol of said second symbol set and a complex conjugate of said symbol;

k) ~~a step of performing complex multiplication~~ of the outputs in said steps i) and j) and delivering a product;

l) ~~a step of detecting~~ the phase of the output in said step k) and delivering said detected phase as a second frequency error of said input signal; and

m) ~~a step of selecting~~ any one of said first and second frequency errors on the basis of a predetermined condition.

18. (original) A frequency error detection method according to claim 17, wherein when said first frequency error is ϕ_1 , said second frequency error is ϕ_2 and a positive reference value preset desirably is ϕ_{th} , said step m) further includes a step of selecting said second frequency error ϕ_2 if an absolute value $|\phi_1|$ of said first frequency error ϕ_1 satisfies $|\phi_1| < \phi_{th}$ but selecting said first frequency error ϕ_1 if $|\phi_1|$ satisfies $|\phi_1| > \phi_{th}$.

19. (currently amended) A method for receiving signals

having the steps a) to m) as recited in claim 18, further comprising the steps
of:

n) ~~a step of performing~~ frequency conversion of a received signal,
converting the received signal subjected to the frequency conversion into a
digital signal and delivering it;

o) ~~a step of delivering~~ a reference frequency signal for said frequency
conversion in said step n);

p) ~~a step of converting~~ the received signal subjected to digital conversion
into a baseband signal to cause it to be applied with quadrature detection and
then delivered;

q) ~~a step of eliminating~~ unwanted frequency components from the
delivered baseband signal;

r) ~~a step of correcting~~ an error between the frequency of the baseband
signal delivered in said step q) and the frequency of said reference frequency
signal based on the basis of the frequency error signal delivered in said step
m) and delivering a corrected baseband signal ~~the corrected error~~;

s) ~~a step of demodulating~~ and delivering the output of the corrected
baseband signal in said step r); and

t) ~~a step of holding~~ the output in said step rs), wherein

wherein the extraction of said first and second symbol sets in said
steps a) and g) is carried out from the signal held in said step t).

20. (currently amended) A method for transmitting and receiving signals having the steps a) to t) as recited in claim 19, further comprising the step of:

a ~~step of~~ converting a signal of baseband zone to be transmitted, which signal is converted into an analog signal, into a signal of radio frequency band on the basis of said reference frequency signal and transmitting the converted radio frequency band signal.

21. (currently amended) An automatic frequency control signal generating circuit comprising:

a frequency error detection unit for extracting at least two known different symbols as a first symbol set from an input signal, further extracting, as a second symbol set, at least two known symbols having a different symbol distance from that of said first symbol set from said input signal, detecting first and second frequency errors of said input signal based on the ~~basis of~~ said extracted first and second symbol sets and delivering them;

a decision unit for deciding in accordance with the ~~error values~~ which one of the ~~outputs of~~ said first and second frequency errors is selected; and

a control signal unit for generating a control signal adapted to control the frequency of said input signal based on the ~~basis of~~ the first or second frequency error selected by said decision unit.

22. (currently amended) An automatic frequency control signal generating circuit according to claim 21, wherein when the a ~~the~~ frame format of said input signal includes a known pilot signal, a data area of predetermined

symbol length and a known synchronous word symbol area of predetermined symbol length, said first symbol set includes said pilot signal and one synchronous word symbol in the synchronous word symbol area and said second symbol set includes two synchronous word symbols in said synchronous word symbol area, wherein said frequency error detection unit further includes:

- a switch unit for selecting and delivering any one of the pilot signal or one synchronous word symbol of said synchronous word symbol area in one frame of said input signal;

- a first multiplier for calculating and delivering a product of the symbol delivered out of said switch unit and a complex conjugate of said symbol;

- a phase inversion unit for inverting and delivering the phase of the value delivered out of said multiplier;

- a second multiplier for calculating and delivering another synchronous word symbol of said synchronous word symbol area and a complex ~~conjugated~~ conjugate of said symbol;

- a third multiplier for performing complex multiplication of the output of said phase inversion unit and the output of said second multiplier and delivering a complex product; and

- a phase detection unit for detecting the phase of the output of said third multiplier and delivering the detected phase as said first or second frequency error, and wherein

- wherein the phase detected by said phase detection unit when said switch selects said pilot signal is made to be said first frequency error and the phase detected by said phase detection unit when said switch unit selects one

synchronous word symbol of said synchronous word symbol area is made to
be said second frequency error.